

| Darwin                   |     |       |              |        |              |       |
|--------------------------|-----|-------|--------------|--------|--------------|-------|
|                          |     | Small | Small/Medium | Medium | Medium/Large | Large |
| Seat Tube                | ST  | 500   | 520          | 535    | 550          | 570   |
| Effective Seat Tube      | EST | 607   | 629          | 641    | 653          | 675   |
| Seat Angle               | SA  | 73.5° | 73.5°        | 73.5°  | 73.5°        | 73.5° |
| Actual Top Tube          | TT  | 521   | 534          | 548    | 564          | 575   |
| Effective Top Tube       | ETT | 541   | 555          | 570    | 585          | 600   |
| Head Tube                | HT  | 150   | 170          | 180    | 190          | 210   |
| Head Angle               | HA  | 70°   | 70.5°        | 71°    | 71.5°        | 72°   |
| Fork A-C                 | AC  | 403   | 403          | 403    | 403          | 403   |
| Fork Offset              | FO  | 50    | 50           | 50     | 50           | 50    |
| Front Centre             | FC  | 612   | 622          | 632    | 642          | 640   |
| Chainstay*               | CS  | 445   | 445          | 445    | 445          | 445   |
| Wheelbase*               | WB  | 1047  | 1057         | 1067   | 1077         | 1075  |
| Bottom Bracket Drop      | BB  | 72    | 72           | 72     | 72           | 72    |
| Reach                    | R   | 368   | 376          | 388    | 400          | 408   |
| Stack                    | S   | 582   | 603          | 615    | 626          | 647   |
| Trail                    | T   | 73    | 70           | 67     | 63           | 60    |
| Standover                | SO  | 759   | 779          | 793    | 804          | 823   |
| Max Tyre (w Mudguards)   |     | 35c   | 35c          | 35c    | 35c          | 35c   |
| Max Tyre (w/o Mudguards) |     | 45c   | 45c          | 45c    | 45c          | 45c   |

Note: All measurements in mm unless otherwise stated. Measurements calculated with maximum tyre size with mudguards and 11.5mm lower headset stack height. Standover measured from 30mm in front of the BB. Darwin frame can be fitted with MT forks to enable use of 29x2.25” tyres. Darwin frame with standard forks can also run with 650Bx47C tyres. \*Dropout allows 15mm of rearward adjustment to increase the chainstay length and wheelbase.

